

1.2M Ku-Band Rx/Tx High Wind Antenna

Series 1984

Technical Specifications

Electrical		Series 2120 Ku-Band
Antenna Size		1.2 M (47.00 in.)
Operating Frequency (GHz)	Receive Transmit	10.95 - 12.75 GHz 13.75 - 14.50 GHz
Midband Gain (+ .2dB)	Receive Transmit	41.50 dBi 43.00 dBi
Antenna Noise Temperature		
20° Elevation		46 K
30° Elevation		43 K
Sidelobe Envelope, Co-Pol (dBi)		
1° < θ < 20°		29 - 25 Log θ dBi
20° < θ < 26.3°		-3.5 dBi
26.3° < θ < 48°		32 - 25 Log θ dBi
48° < θ		-10 dBi (averaged)
Cross-Polarization		
On Axis		-35 dB Max.
Within B.P.E		-30 dB Max.
VSWR		1.3:1 Max.

Mechanical	
Reflector Material	Glass Fiber Reinforced Polyester SMC
Antenna Optics	Single Piece Offset, Prime Focus
Mast Pipe Size	2.50" Sch 40 Pipe (2.88" OD) 73.2 mm (72mm min., 74mm max.)
Elevation Adjustment Range	5° - 90° Continuous Fine Adjust
Azimuth Adjustment Range	360° Cont. Coarse Adj., $\pm 15^\circ$ Fine Adjust
Polarization Adjustment Range	$\pm 90^\circ$ Continuous Coarse Adjust
Maximum Transmitter Weight	12 lbs.
Feed Support Tailpiece	Available as needed
Shipping Specifications	90 lbs. (41 kg.)

Environmental Performance		
Wind Loading	Operational Survival Survival (no perm. damage) Survival (no breakaway)	65 mph (104 km/h) 90 mph (144 km/h) 125 mph (201 km/h) 150 mph (240 km/h)
Temperature	Operational Survival	-40° to 140° F (-40° to 60° C) -50° to 160° F (-46° to 71° C)
Rain	Operational Survival	1/2"/hr 2"/hr
Ice	Operational Survival	----- 1/2" radial
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation		360 BTU/h/ft ²

GENERAL DYNAMICS SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-024 Rev. 05/11